

3/4.6 CONTAINMENT SYSTEMS

BASES

3/4.6.1 PRIMARY CONTAINMENT

3/4 6.1.1 CONTAINMENT INTEGRITY

Primary CONTAINMENT INTEGRITY ensures that the release of radioactive materials from the containment atmosphere will be restricted to those leakage paths and associated leak rates assumed in the accident analyses. This restriction, in conjunction with the leakage rate limitation, will limit the site boundary radiation doses to within the limits of 10 CFR 100 during accident conditions.

The purpose of this surveillance requirement (4.6.1.1a) is not to perform any testing or valve manipulations, but to verify that containment isolation valves capable of being mispositioned are in their proper safety position (closed).

Valves and blind flanges in high radiation areas may be verified by use of administrative controls. Allowing the use of administrative means to verify compliance with the surveillance requirement for these valves is acceptable based on the limited access to these areas in Modes 1, 2, 3, and 4 for ALARA reasons. Therefore, the probability of misalignment of these containment isolation valves, once they have been verified in the proper position, is small.

Use of administrative means to verify position of valves and blind flanges that are locked, sealed or otherwise secured is acceptable for Surveillance Requirement 4.6.1.1.a. Allowing verification by administrative means is considered acceptable, since the function of locking, sealing, or securing components is to ensure that these devices are not inadvertently repositioned. Therefore, the probability of misalignment of these components, once they have been verified to be in the proper position, is low.

The service water accumulator vessel and discharge valves function to maintain water filled, subcooled fluid conditions in the containment fan coil unit (CFCU) cooling loops during accident conditions. The service water accumulator vessel and discharge valves were installed to address the Generic Letter 96-06 issues of column separation waterhammer and two phase flow during an accident involving a loss of offsite power. The operability of each service water accumulator vessel and discharge valve is required to ensure the integrity of containment penetrations associated with the containment fan coil units during accident conditions. If a service water accumulator vessel does not meet the vessel surveillance requirements, or if the discharge valve response time does not meet design acceptance criteria when tested in accordance with procedures, the containment integrity requirements of the CFCU cooling loops exclusively supplied by the inoperable accumulator vessel or discharge valve are not met. Limiting Condition for Operation 3.6.1.1 is applicable, and the cooling loops for the two CFCU's exclusively supplied by the inoperable accumulator are to be removed from service and isolated to maintain containment integrity.

3/4 6.1.2 CONTAINMENT LEAKAGE

The limitations on containment leakage rates ensure that the total containment leakage volume will not exceed the value assumed in the accident analyses at the peak accident pressure P_a . As an added conservatism, the measured overall integrated leakage rate (Type A test) is further limited to less than or equal to $0.75 L_a$ or less than or equal to $0.75 L_t$, as applicable, during performance of the periodic test to account for possible degradation of the containment leakage barriers between leakage tests.

3/4 .6 CONTAINMENT SYSTEMS

BASES

The surveillance testing for measuring leakage rates are consistent with the Containment Leakage Rate Testing Program.

3/4.6.1.3 CONTAINMENT AIR LOCKS

Containment air locks form part of the containment pressure boundary and provide a means for personnel access during all MODES of operation.

Each air lock is nominally a right circular cylinder, 10 feet in diameter, with a door at each end. The doors are interlocked during normal operation to prevent simultaneous opening.

During periods when containment is not required to be OPERABLE, the door interlock mechanism may be disabled, allowing both doors of an air lock to remain open for extended periods when frequent containment entry is necessary. Each air lock door has been designed and tested to certify its ability to withstand a pressure in excess of the maximum expected pressure following a Design Basis Accident (DBA) in containment. As such, closure of a single door supports containment OPERABILITY. Each of the doors contains double gasketed seals and local leakage rate testing capability to ensure pressure integrity. To effect a leak tight seal, the air lock design uses pressure-seated doors (i.e., an increase in containment internal pressure results in increased sealing force on each door).

Each personnel air lock is provided with limit switches on both doors that provide control room indication of door position. Additionally, control room indication is provided to alert the operator whenever an air lock door interlock mechanism is defeated.

The containment air locks form part of the containment pressure boundary. As such, air lock integrity and leak tightness is essential for maintaining the containment leakage rate within limit in the event of a DBA. Not maintaining air lock integrity or leak tightness may result in a leakage rate in excess of that assumed in the unit safety analysis.

The DBAs that result in a release of radioactive material within containment are a loss of coolant accident and a rod ejection accident. In the analysis of each of these accidents, it is assumed that containment is OPERABLE such that release of fission products to the environment is controlled by the rate of containment leakage. The containment was designed with an allowable leakage rate of 0.1% of containment air weight per day. This leakage rate is defined in 10CRF50, Appendix J as $L_a = 0.1\%$ of containment air weight per day, the maximum allowable containment leakage rate at the calculated peak containment internal pressure $P_a = 47.0$ psig following a DBA. The allowable leakage rate forms the basis for the acceptance criteria imposed on the surveillance requirements associated with the air locks.

Each containment air lock forms part of the containment pressure boundary. As part of the containment, the air lock safety function is related to control of the containment leakage rate resulting from DBA. Thus, each air lock's structural integrity and leak tightness are essential to the successful mitigation of such an event.

Each air lock is required to be OPERABLE. For the air lock to be considered OPERABLE, the air lock interlock mechanism must be OPERABLE, the air lock must be in compliance with the Type B air lock leakage test, and both air lock doors must be OPERABLE. The interlock allows only one air lock door of an air lock to be opened at one time. This

3/4.6 CONTAINMENT SYSTEMS

BASES

provision ensures that a gross breach of containment does not exist when containment is required to be OPERABLE. Closure of a single door in each air lock is sufficient to provide a leak tight barrier following postulated events. Nevertheless, both doors are kept closed when the air lock is not being used for normal entry into and exit from containment.

In MODES 1, 2, 3, and 4, a DBA could cause a release of radioactive material to containment. In MODES 5 and 6, the probability and consequences of these events are reduced due to the pressure and temperature limitations of these MODES. Therefore, the containment air locks are not required in MODE 5 to prevent leakage of radioactive material from containment. The requirements for the containment air locks during MODE 6 are addressed in LCO 3.9.4, "Containment Building Penetrations".

The ACTIONS are modified by five notes. Note (1) allows entry and exit to perform repairs on the affected air lock component. If the outer door is inoperable, then it may be easily accessed for most repairs. It is preferred that the air lock be accessed from inside primary containment by entering through the other OPERABLE air lock. However, if this is not practicable, or if repairs on either door must be performed from the barrel side of the door then it is permissible to enter the air lock through the OPERABLE door, which means there is a short time during which the containment boundary is not intact (during access through the OPERABLE door). The ability to open the OPERABLE door, even if it means the containment boundary is temporarily not intact, is acceptable due to the low probability of an event that could pressurize the containment during the short time in which the OPERABLE door is expected to be open. After each entry and exit, the OPERABLE door must be immediately closed. If ALARA conditions permit, entry and exit should be via an OPERABLE air lock.

Note (2) adds clarification that separate condition entry is allowed for each air lock. This is acceptable, since the required ACTIONS provide appropriate compensatory measures for each inoperable air lock. Complying with the Required Actions may allow for continued operation. A subsequent inoperable air lock is governed by condition entry for that air lock.

Notes (3) and (4) ensure that only the required ACTIONS and associated completion times of condition c. are required if both doors in the same air lock are inoperable. With both doors in the same air lock inoperable, an OPERABLE door is not available to be closed. Required ACTIONS c.1 and c.2 are the appropriate remedial actions. The exception of these Notes does not affect tracking the completion time from the initial entry into condition a., only the requirement to comply with the required ACTIONS.

In the event the air lock leakage results in exceeding the overall containment leakage rate, Note (5) directs entry into the applicable Conditions and required ACTIONS of LCO 3.6.1, "Primary Containment".

With one air lock door in one or more containment air locks inoperable, the OPERABLE door must be verified closed (ACTION a.1) in each affected containment air lock. This ensures that a leak tight containment barrier is maintained by the use of an OPERABLE air lock door. This ACTION must be completed within 1 hour. The specified time period is consistent with the ACTIONS of LCO 3.6.1.1 that requires that containment be restored to OPERABLE status within 1 hour. OPERABILITY of the air lock interlock is not required to support the OPERABILITY of an air lock door.

3/4.6 CONTAINMENT SYSTEMS

BASES

In addition, the affected air lock penetration must be isolated by locking closed the OPERABLE air lock door within the 24 hour completion time (ACTION a.2). The 24 hour completion time is reasonable for locking the OPERABLE air lock door, considering the OPERABLE door of the affected air lock is being maintained closed.

Required ACTION a.3 verifies that an air lock with an inoperable door has been isolated by the use of a locked and closed OPERABLE air lock door. This ensures that an acceptable containment leakage boundary is maintained. The completion time of once per 31 days is based on engineering judgement and is considered adequate in view of the low likelihood of a locked door being mispositioned and other administrative controls.

ACTION a.3 allows the use of the air lock for entry and exit for 7 days under administrative controls if both air locks have an inoperable door. This 7-day restriction begins when the second air lock is discovered to be inoperable.

Containment entry may be required on a periodic basis to perform Technical Specification Surveillances and required ACTIONS, as well as other activities on equipment inside containment that are required by Technical Specifications or activities on equipment that support Technical Specification required equipment. This Note is not intended to preclude performing other activities (i.e., non-Technical Specification required activities) if the containment is entered, using the inoperable air lock, to perform an allowed entry listed above. This allowance is acceptable due to the low probability of an event that could pressurize the containment during the short time that the OPERABLE door is expected to be open.

Because of ALARA considerations, ACTION a.3 also allows air lock doors located in high radiation areas to be verified locked closed by use of administrative means. Allowing verification by administrative means is considered acceptable, since access to these areas is typically restricted. Therefore, the probability of misalignment of the door, once it has been verified to be in the proper position, is small.

With an air lock interlock mechanism inoperable in one or more air locks, the required ACTIONS and associated completion times are consistent with those specified in Condition a. In addition, ACTION b.3 allows entry into and exit from containment under the control of a dedicated individual stationed at the air lock to ensure that only one door is opened at a time (i.e., the individual performs the function of the interlock). In addition, ACTION b.3 allows air lock doors located in high radiation areas to be verified locked closed by use of administrative means.

ACTION c.1 requires that with one or more air locks inoperable for reasons other than those described in condition a. or b., action must be initiated immediately to evaluate previous combined leakage rates using current air lock test results. An evaluation is acceptable, since it is overly conservative to immediately declare the containment inoperable if both doors in an air lock have failed a seal test or if the overall air lock leakage is not within limits. In many instances (e.g., only one seal per door has failed), containment remains OPERABLE, yet only 1 hour (per LCO 3.6.1.1) would be provided to restore the air lock door to OPERABLE status prior to requiring plant shutdown. In addition, even with both doors failing the seal test, the overall containment leakage rate can still be within limits.

3/4.6 CONTAINMENT SYSTEMS

BASES

Required ACTION c.2 requires that one door in the affected containment air lock must be verified to be closed within the 1 hour completion time. This specified time period is consistent with the ACTIONS of LCO 3.6.1.1, which requires that containment be restored to OPERABLE status within 1 hour.

Additionally, the affected air lock(s) must be restored to OPERABLE status within the 24 hour completion time. This completion time begins at the time that the air lock is discovered to be inoperable. The specified time period is considered reasonable for restoring an inoperable air lock to OPERABLE status, assuming that at least one door is maintained closed in each affected air lock.

If the inoperable containment air lock cannot be restored to OPERABLE status within the required completion time, the plant must be brought to a MODE in which the LCO does not apply. To achieve this status, the plant must be brought to at least Hot Standby within 6 hours and to Cold Shutdown within the following 30 hours. The allowed completion times are reasonable based on operating experience, to reach the required plant conditions from full power conditions in an orderly manner and without challenging plant systems.

Maintaining containment airlocks OPERABLE requires compliance with the leakage rate test requirements of 10CFR50, Appendix J, as modified by approved exemptions. This Surveillance Requirement reflects the leakage rate testing requirements with regard to air lock leakage (Type B leakage tests). The acceptance criteria were established during initial air lock and containment OPERABILITY testing. The periodic testing requirements verify that the air lock leakage does not exceed the allowed fraction of the overall containment leakage rate. The frequency is required by Appendix J, as modified by approved exemptions. Thus, the provision of Specification 4.0.2 (which allows frequency extensions) does not apply.

The air lock interlock is designed to prevent simultaneous opening of both doors in a single air lock. Since both the inner and outer doors of an air lock are designed to withstand the maximum expected post accident containment pressure, closure of either door will support containment OPERABILITY. Thus, the door interlock feature supports containment OPERABILITY while the air lock is being used for personnel transit in and out of the containment. Periodic testing of this interlock demonstrates that the interlock will function as designed and that simultaneous opening of the inner and outer doors will not inadvertently occur. The Surveillance Frequency is based on operating experience, equipment reliability, and plant risk and is controlled under the Surveillance Frequency Control Program.

CONTAINMENT SYSTEMS

BASES

3/4.6.1.4 INTERNAL PRESSURE

The limitations on containment internal pressure ensure that: 1) the containment structure is prevented from exceeding its design negative pressure differential with respect to the outside atmosphere of 3.5 psig, and 2) the containment peak pressure does not exceed the design pressure of 47 psig during the limiting pipe break conditions. The pipe breaks considered are LOCA and steam line breaks.

The limit of 0.3 psig for initial positive containment pressure is consistent with the accident analyses initial conditions.

The maximum peak pressure expected to be obtained from a LOCA or steam line break event is ≤ 47 psig.

3/4.6.1.5 AIR TEMPERATURE

The limitations on containment average air temperature ensure that the overall containment average air temperature does not exceed the initial temperature condition assumed in the accident analysis for a LOCA or steam line break. In order to determine the containment average air temperature, an average is calculated using measurements taken at locations within containment selected to provide a representative sample of the overall containment atmosphere.

3/4.6.1.6 CONTAINMENT STRUCTURAL INTEGRITY

This limitation ensures that the structural integrity of the containment will be maintained comparable to the original design standards for the life of the facility. Structural integrity is required to ensure that the containment will withstand the design pressure. The visual inspections of the concrete and liner and the Type A leakage test, both in accordance with the Containment Leakage Rate Testing Program, are sufficient to demonstrate this capability.

(Note that the elements of 3/4.6.1.7 were RELOCATED to 3/4 6.3 by LCR S06-06)

CONTAINMENT SYSTEMS

BASES

3/4.6.2 DEPRESSURIZATION AND COOLING SYSTEMS

3/4.6.2.1 CONTAINMENT SPRAY SYSTEM

The OPERABILITY of the containment spray system, when operated in conjunction with the Containment Cooling System, ensures that containment depressurization and cooling capability will be available in the event of a LOCA. The pressure reduction and resultant lower containment leakage rate are consistent with the assumptions used in the accident analyses.

The containment spray system also provides a mechanism for removing iodine from the containment atmosphere and therefore the time requirements for restoring an inoperable spray system to OPERABLE status have been maintained consistent with that assigned other inoperable ESF equipment.

Normal plant operation and maintenance practices are not expected to trigger surveillance requirement 4.6.2.1.d. Only an unanticipated circumstance would initiate this surveillance, such as inadvertent spray actuation, a major configuration change, or a loss of foreign material control when working within the affected boundary of the system. If an activity occurred that presents the potential of creating nozzle blockage, an evaluation would be performed by the engineering organization to determine if the amount of nozzle blockage would impact the required design capabilities of the containment spray system. If the evaluation determines that the containment spray system would continue to perform its design basis function, then performance of the air or smoke flow test would not be required. If the evaluation cannot conclusively determine the impact to the containment spray system, then the air or smoke flow test would be performed to determine if any nozzle blockage has occurred.

3/4.6.2.2 SPRAY ADDITIVE SYSTEM

The OPERABILITY of the spray additive system ensures that sufficient NaOH is added to the containment spray in the event of a LOCA. The limits on NaOH volume and concentration, ensure that 1) the iodine removal efficiency of the spray water is maintained because of the increase in pH value, and 2) corrosion effects on components within containment are minimized. The contained water volume limit includes an allowance for water not usable because of tank discharge line location or other physical characteristics. These assumptions are consistent with the iodine removal efficiency assumed in the accident analyses.

3/4.6.2.3 CONTAINMENT COOLING SYSTEM

The OPERABILITY of the containment cooling system ensures that adequate heat removal capacity is available when operated in conjunction with the containment spray systems during post-LOCA conditions.

Five containment fan cooler units (CFCUs) are provided. Two CFCUs are each supplied with cooling water from one of the two separate service water headers. One CFCU is supplied from both service water headers through normally open isolation valves and check valves from each header. Air is drawn into the coolers through the fan and discharged to duct work which distributes the cooled air to the various containment compartments and areas.

During normal operation, up to four CFCUs are typically operating. The fans are normally operated at high speed with service water supplied to the cooling coils. The CFCUs are designed to limit the ambient containment air temperature during normal unit operation to less than the limit specified in LCO 3.6.1.5, "Air Temperature." This temperature limitation ensures that the containment temperature does not exceed the initial temperature conditions assumed for the DBAs.

In post-accident operation following an actuation signal, the CFCUs are designed to start automatically in low speed if not already running. If running in high (normal) speed, the fans automatically shift to low speed. The fans are operated at the lower speed during accident conditions to prevent motor overload from the higher mass atmosphere.

CONTAINMENT SYSTEMS

BASES

The surveillance requirements for the service water accumulator vessels ensure each tank contains sufficient water and nitrogen to maintain water filled, subcooled fluid conditions in three containment fan coil unit (CFCU) cooling loops in response to a loss of offsite power, without injecting nitrogen converges into the containment fan coil unit loops assuming the most limiting single failure. The surveillance requirement for the discharge valve response time test ensures that on a loss of offsite power, each discharge valve actuates to the open position in accordance with the design to allow sufficient tank discharge into the CFCU piping to maintain water filled subcooled fluid conditions in three CFCU cooling loops, assuming the most limiting single failure.

The surveillance requirements for the CFCUs ensure sufficient SWS flow through each operating cooler to provide the minimum containment cooling as assumed by the containment response analysis for a design-basis LOCA or MSLB event. The surveillance flow rate is selected to ensure adequate heat removal (with no two-phase flow). The specified surveillance flow rate represents the total flow from both the CFCU coils and the CFCU motor-cooler

SR 4.6.2.3.b.2

Operating each CFCU in low speed for ≥ 15 minutes ensures that all CFCUs are OPERABLE and that all associated controls are functioning properly. It also ensures that blockage, fan or motor failure can be detected for corrective action.

SR 4.6.2.3.c.1

This SR requires verification that each CFCU actuates upon receipt of an actual or simulated safety injection signal.

3/4.6.3 CONTAINMENT ISOLATION VALVES

The OPERABILITY of the containment isolation valves ensures that the containment atmosphere will be isolated from the outside environment in the event of a release of radioactive material to the containment atmosphere or pressurization of the containment. Containment isolation within the time limits specified ensures that the release of radioactive material to the environment will be consistent with the assumptions used in the analyses for a LOCA.

The opening of locked or sealed closed containment isolation valves (penetration flow paths) on an intermittent basis under administrative control includes the following considerations: (1) stationing a dedicated individual, who is in constant communication with the control room, at the valve controls, (2) instructing this individual to close these valves in an accident situation, and (3) assuring that the environmental conditions will not preclude access to close the valves and that this action will prevent the release of radioactivity outside the containment.

The main steam isolation valves (MSIVs) fulfill their containment isolation function as remote-manual containment isolation valves. The automatic closure of the MSIVs is not required for containment isolation due to having a closed system inside containment. The remote-manual containment isolation function of the MSIVs can be accomplished through either the use of the hydraulic operator or when the MSIV has been tested in accordance with surveillance requirement 4.7.1.5 the steam assist closure function can be credited.

CONTAINMENT SYSTEMS

BASES

Surveillance Requirement (SR) 4.6.3.3 only applies to the MS7 (Main Steam Drain) valves and the MS18 (Main Steam Bypass) valves. The MS167 (Main Steam Isolation) valves are tested for main steam isolation purposes by SR 4.7.1.5. For containment isolation purposes, the MS167s are tested as remote/manual valves pursuant to Specification 4.0.5.

The containment purge supply and exhaust isolation valves are required to be closed during plant operation since these valves have not been demonstrated capable of closing during a LOCA. Maintaining these valves (or equivalent isolation device) closed during plant operations ensures that excessive quantities of radioactive materials will not be released via the containment purge system.

A containment purge valve is not a required containment isolation valve when its flow path is isolated with a blind flange tested in accordance with SR 4.6.1.2.b. The inboard valve of both the containment purge supply and exhaust penetrations has been replaced with a testable double o-ring blind flange. The blind flange serves as the containment boundary and performs the containment integrity function in Modes 1, 2, 3, and 4. The outboard valve of both the containment purge supply and exhaust penetrations performs no containment integrity function in MODES 1-4; these valves operate during shutdown for normal system purging and containment closure when the blind flanges are removed.