

CONTAINMENT SYSTEMS

3/4.6.3 CONTAINMENT ISOLATION VALVES

LIMITING CONDITION FOR OPERATION

3.6.3 Each containment isolation valve shall be OPERABLE.

APPLICABILITY: MODES 1, 2, 3 and 4.

ACTION:

NOTE 1

Penetration flow paths, except for the containment purge valves, may be unisolated intermittently under administrative controls.

Note 2

A containment purge valve is not a required containment isolation valve when its flow path is isolated with a testable blind flange tested in accordance with SR 4.6.1.2.b. The *required* containment purge supply and exhaust isolation valves shall be closed. (Valves immobilized in shut position with control air to valve operators isolated and tagged out of service).

NOTE 3

The containment pressure-vacuum relief isolation valves may be opened on an intermittent basis, under administrative control, as necessary to satisfy the requirement of Specification 3.6.1.4.

1. With one or more of the containment isolation valve(s) inoperable, maintain at least one isolation valve OPERABLE in each affected penetration that is open and either:
 - a. Restore the inoperable valve(s) to OPERABLE status within 4 hours, or
 - b. Isolate each affected penetration within 4 hours by use of at least one deactivated automatic valve secured in the isolation position, or
 - c. Isolate each affected penetration within 4 hours by use of at least one closed manual valve or blind flange; or
 - d. Be in at least HOT STANDBY within the next 6 hours and in COLD SHUTDOWN within the following 30 hours.
2. With one required containment purge supply and/or exhaust isolation valve open, close the open valve(s) within one hour or be in at least HOT STANDBY within the next 6 hours and in COLD SHUTDOWN within the following 30 hours.

SURVEILLANCE REQUIREMENTS

4.6.3.1 DELETED

CONTAINMENT SYSTEMS

SURVEILLANCE REQUIREMENTS (Continued)

4.6.3.2 Each containment isolation valve shall be demonstrated OPERABLE during the COLD SHUTDOWN or REFUELING MODE in accordance with the Surveillance Frequency Control Program by:

- a. Verifying that on a Phase A containment isolation test signal, each Phase A isolation valve actuates to its isolation position.
- b. Verifying that on a Phase B containment isolation test signal, each Phase B isolation valve actuates to its isolation position.
- c. NOT USED
- d. Verifying that on a Containment Purge and Pressure-Vacuum Relief isolation test signal, each required Purge and each Pressure-Vacuum Relief valve actuates to its isolation position.
- e. Verifying that the Containment Pressure-Vacuum Relief Isolation valves are limited to $\leq 60^\circ$ opening angle.

4.6.3.3 In accordance with the Surveillance Frequency Control Program, verify that on a main steam isolation test signal, each main steam isolation valve actuates to its isolation position.

4.6.3.4 The isolation time of each power operated or automatic containment isolation valve shall be determined to be within its limit when tested pursuant to the INSERVICE TESTING PROGRAM.

4.6.3.5 Each required containment purge isolation valve shall be demonstrated OPERABLE within 24 hours after each closing of the valve, except when the valve is being used for multiple cyclings, then in accordance with the Surveillance Frequency Control Program, by verifying that when the measured leakage rate is added to the leakage rates determined pursuant to Specification 4.6.1.2.b for all other Type B and C penetrations, the combined leakage rate is less than or equal to 0.60La.

4.6.3.6 A pressure drop test to identify excessive degradation of resilient valve seals shall be conducted on the:

- a. Required Containment Purge Supply and Exhaust Isolation Valves in accordance with the Surveillance Frequency Control Program.
- b. Deleted.

4.6.3.7 The required containment purge supply and exhaust isolation valves shall be determined closed in accordance with the Surveillance Frequency Control Program.

PAGES 3/4 6-16 THROUGH 3/4 6-22 ARE INTENTIONALLY BLANK.